



## Vireurs pour soudage avec vitesse variable

<b>Maximum capacity/ Belastung/ Portata massima [da N]</b>	<b>25000</b>
<b>Total approx Weight/ Gewicht/ Peso totale appross. [da N]</b>	<b>1900</b>
<b>Tilting angle/ Kippwinkel/ Inclinazione [°]</b>	<b>600/ 5350</b>
<b>Max Torque Moment/ Drehmoment/ M Torcente [daNm]</b>	<b>Ø400- 300</b>
<b>Max Tilting Moment/ Kippmoment/ M flettente[da Nm]</b>	<b>2200</b>
<b>Table Rotation speed/ Drehgeschwindigkeit/ Velocità di rotazione [min-max U/min]</b>	<b>500</b>
<b>Voltage/ Spannung/ Voltaggio[V]</b>	<b>0,22/ 0,91</b>
<b>Electric power/ Anschlußleistung/ Potenza elettrica [kW]</b>	<b>3/400</b>
<b>Ground-block/ Massekupplung/ Messa a terra [A]</b>	<b>1,1</b>
<b>Overall size (approx.) x table Ø x H/ Abmessungen ca. x Ø Planscheibe x H/ Ingombri di massima x Ø tavola x A [mm]</b>	<b>3394x 1000x H 770</b>

